



# STP® CONVENTIONAL GREEN ANTIFREEZE/COOLANT



## TECHNICAL DATA

Since 1954, STP® has been the premier American brand name for automotive additives, lubricants and performance products in the USA. STP® Conventional Green Antifreeze/Coolant is a universal, conventional green formulation that meets or exceeds ASTM requirements. This superior quality, ethylene glycol-based engine coolant is low in silicates. It protects all cooling system metals including aluminum, as well as rubber hoses, gaskets and plastics. Recommended for initial fill or top-off in all gasoline and diesel engines where conventional formulations are in use or are required.

Performance, Features & Benefits:	<ul style="list-style-type: none"><li>• Protects against winter freezing and summer boil over</li><li>• Prevents pitting caused by cavitation and corrosion of brass, copper, solder, steel, cast iron and aluminum</li><li>• Compatible with most major American brands of conventional antifreeze/coolant</li></ul>	
Package Size Offerings	Concentrate 3x1 Case	Part #11071
	Concentrate Drum	Part #10214
	Concentrate Tote	Part #10212
	Ready-To-Use 3x1 Case	Part #11072
	Ready-To-Use Drum	Part #10220
	Ready-To-Use Tote	Part #10217
Aluminum Compatibility	Yes	
Contains Bitterant	Yes	
Base Fluid	100% Virgin Ethylene Glycol	
pH, 50% Volume Solution	10.0-11.0	
Product Color	Green	
Specifications, Approvals & Recommendations**	ASTM D3306 ASTM D4985 SAE J1941 <i>*For a full list of performance specifications, visit <a href="http://www.stpcoolant.com">www.stpcoolant.com</a>. *Meets most performance requirements but may or may not meet certain chemical requirements.</i>	
Recommended Change Interval	Up to 2 Years/50,000 Miles	



KOST® USA, Inc. recommends to always properly dispose of spent coolant. Contact your state or local municipality for instructions on proper disposal to protect our environment. If a coolant spill occurs, call local authorities and ask for proper instruction on how to clean up the spill.

All reasonable care has been taken to ensure that the information herein is accurate as of the date of printing. The test results listed are typical properties only. Formula and blending changes may result in slight color and appearance changes.

STPPDS02082016